

1 Identification

1.1 Product identifier

- Trade name: **SPRAY LENS CLEAR**
- Article number: 708
- Application of the substance / the mixture Surface protection

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:
H.B. BODY S.A
B' ENTRANCE BLOCK 50 DA9 & MB6 Str
THESSALONIKI INDUSTRIAL AREA
57.022, SINDOS
THESSALONIKI,GREECE
Ph: +30 2310 790 000
Fax: +30 2310 790 033
email: hbbody@hbbody.com

- Information department:
HB BODY S.A.
B' ENTRANCE BLOCK 50 DA9 & MB6 Str
THESSALONIKI INDUSTRIAL AREA
57.022, SINDOS
THESSALONIKI,GREECE
Ph: +30 2310 790 000
Fax: +30 2310 790 033
www.hbbody.com
email: hbbody@hbbody.com

- **1.4 Emergency telephone number:** CHEMTRECK : 800-494-9300

2 Hazard(s) identification

2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008



GHS02 Flame

Flammable Aerosols 1

H222

Extremely flammable aerosol.



GHS04 Gas cylinder

Gases under Pressure - Compressed gas

H280

Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Specific Target Organ Toxicity - Repeated Exposure 2 H373

May cause damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

Eye Damage 1

H318

Causes serious eye damage.

(Contd. on page 2)

US

Trade name: SPRAY LENS CLEAR

(Contd. of page 1)



GHS07

Acute Toxicity - Oral 4	H302	Harmful if swallowed.
Acute Toxicity - Inhalation 4	H332	Harmful if inhaled.
Skin Irritation 2	H315	Causes skin irritation.
Sensitization - Skin 1	H317	May cause an allergic skin reaction.
Specific Target Organ Toxicity - Single Exposure 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labeled according to the CLP regulation.
- Hazard pictograms



GHS02



GHS04



GHS05



GHS07



GHS08

- Signal word Danger
- Hazard-determining components of labeling:
butan-1-ol
Solvent naphtha (petroleum), light arom.
a mass reaction of ethyl benzene and xylene
3-aminomethyl-3,5,5-trimethylcyclohexylamine
4,4'-methylenebis(cyclohexylamine)

Hazard statements

H222	Extremely flammable aerosol.
H280	Contains gas under pressure; may explode if heated.
H302+H332	Harmful if swallowed or if inhaled.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.
H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves / eye protection / face protection.
P301+P312	If swallowed: Call a poison center/doctor if you feel unwell.
P302+P352	If on skin: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P321	Specific treatment (see on this label).
P314	Get medical advice/attention if you feel unwell.

(Contd. on page 3)
US

Trade name: SPRAY LENS CLEAR

(Contd. of page 2)

- P330 Rinse mouth.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P410+P403 Protect from sunlight. Store in a well-ventilated place.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- NFPA ratings (scale 0 - 4)



- HMIS-ratings (scale 0 - 4)



- **2.3 Other hazards**
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

3.2 Chemical characterization: Mixtures

- Description: Mixture of the substances listed below with nonhazardous additions.






Dangerous components:

CAS: 115-10-6	dimethyl ether	40-<45%
EINECS: 204-065-8	Flammable Gases 1, H220	
Index number: 603-019-00-8	Gases under Pressure - Compressed gas, H280	
RTECS: PM 4780000	Acute Toxicity - Inhalation 2, H330	
CAS: 71-36-3	butan-1-ol	15-<20%
EINECS: 200-751-6	Flammable Liquids 3, H226	
Index number: 603-004-00-6	Eye Damage 1, H318	
RTECS: EO 1400000	Acute Toxicity - Oral 4, H302; Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H335-H336	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	≥15-<20%
EINECS: 265-199-0	Flammable Liquids 3, H226	
Index number: 649-356-00-4	Aspiration Hazard 1, H304	
	Acute Toxicity - Inhalation 4, H332; Specific Target Organ Toxicity - Single Exposure 3, H335	
CAS: 78-92-2	butanol	≥1-<10%
EINECS: 201-158-5	Flammable Liquids 3, H226	
Index number: 603-127-00-5	Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335-H336	
RTECS: EO 1750000		
CAS: 1330-20-7	xylene	5-<10%
Index number: 601-022-00-9	Flammable Liquids 3, H226	
	Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315	

(Contd. on page 4)
US

Trade name: SPRAY LENS CLEAR

(Contd. of page 3)

EC number: 905-588-0	a mass reaction of ethyl benzene and xylene	≥1-<5%
	 Flammable Liquids 3, H226	
	 Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304	
	 Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335	
CAS: 2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	≥0.001-<0.1%
EINECS: 220-666-8	 Skin Corrosion 1B, H314; Eye Damage 1, H318	
Index number: 612-067-00-9	 Acute Toxicity - Oral 4, H302; Sensitization - Skin 1A, H317	

4 First-aid measures

4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation:
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Immediately call a doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

5.1 Extinguishing media

- Suitable extinguishing agents:
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

- Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products
- Protective equipment: Mouth respiratory protective device.
- Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Use neutralizing agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 5)

Trade name: SPRAY LENS CLEAR

(Contd. of page 4)

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

-
- 115-10-6 dimethyl ether: 3,000 ppm
 - 71-36-3 butan-1-ol: 60 ppm
 - 78-92-2 butanol: 150 ppm
 - 1330-20-7 xylene: 130 ppm
 - 1330-20-7 xylene: 130 ppm

· **PAC-2:**

-
- 115-10-6 dimethyl ether: 3800* ppm
 - 71-36-3 butan-1-ol: 800 ppm
 - 78-92-2 butanol: 220 ppm
 - 1330-20-7 xylene: 920* ppm
 - 1330-20-7 xylene: 920* ppm

· **PAC-3:**

-
- 115-10-6 dimethyl ether: 7200* ppm
 - 71-36-3 butan-1-ol: 8000** ppm
 - 78-92-2 butanol: 10000** ppm
 - 1330-20-7 xylene: 2500* ppm
 - 1330-20-7 xylene: 2500* ppm

7 Handling and storage

· **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

· **Information about protection against explosions and fires:**

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep receptacle tightly sealed.

· **7.3 Specific end use(s)** No further relevant information available.

* **8 Exposure controls/personal protection**

· **8.1 Control parameters**

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

115-10-6 dimethyl ether

WEEL Long-term value: 1000 ppm

71-36-3 butan-1-ol

PEL Long-term value: 300 mg/m³, 100 ppm

(Contd. on page 6)
US

Trade name: SPRAY LENS CLEAR

(Contd. of page 5)

REL Ceiling limit value: 150 mg/m³, 50 ppm
Skin

TLV Long-term value: 20 ppm

78-92-2 butanol

PEL Long-term value: 450 mg/m³, 150 ppm

REL Short-term value: 455 mg/m³, 150 ppm
Long-term value: 305 mg/m³, 100 ppm

TLV Long-term value: 100 ppm

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 20 ppm
BEI, A4

· **Regulatory information**

WEEL: Guide to Occupational Exposure Values (AIHA WEELs)

PEL: Guide to Occupational Exposure Values (OSHA PELs)

REL: Guide to Occupational Exposure Values (NIOSH RELs)

TLV: Guide to Occupational Exposure Values (TLV)

· **Ingredients with biological limit values:**

1330-20-7 xylene

BEI 1.5 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

· **Additional information:** The lists that were valid during the creation were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 7)

Trade name: SPRAY LENS CLEAR

(Contd. of page 6)

- Penetration time of glove material
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
Rubber gloves
- Eye protection:
Safety glasses



Tightly sealed goggles

- Body protection: Protective work clothing

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

- Form: Aerosol
- Color: Clear
- Odor: Characteristic
- Odor threshold: Not determined.
- pH-value: Not determined.

· Change in condition

- Melting point/Melting range: Undetermined.
- Boiling point/Boiling range: -24.9 °C (-12.8 °F)
- Flash point: < 23 °C (< 73.4 °F)

· Flammability (solid, gaseous):

Not applicable.

· Decomposition temperature:

Not determined.

· Ignition temperature:

Product is not selfigniting.

· Danger of explosion:

Risk of explosion by shock, friction, fire or other sources of ignition.

· Explosion limits:

- Lower: 0.7 Vol %
- Upper: 9.4 Vol %

· Vapor pressure at 20 °C (68 °F): 6.7 hPa (5 mm Hg)

· Density at 20 °C (68 °F): 0.7731 g/cm³ (6.45152 lbs/gal)

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with

- Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

- Dynamic: Not determined.
- Kinematic: Not determined.

(Contd. on page 8)
US

Trade name: SPRAY LENS CLEAR

(Contd. of page 7)

- Solvent content:
 - Organic solvents: 87.7-95.1 %
 - VOC content: 87.71-95.11 %
735.3 g/l / 6.14 lb/gal
 - Solids content: 0.2 %
- **9.2 Other information** No further relevant information available.

10 Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

* **11 Toxicological information**

- **11.1 Information on toxicological effects**
 - Acute toxicity:
Harmful if swallowed or if inhaled.
 - LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 >1,088 mg/kg (rat)
Dermal LD50 >6,696-<15,308 mg/kg
Inhalative LC50/4 h >17.3-<31.1 mg/l

115-10-6 dimethyl ether

Inhalative LC50/4 h 308 mg/l (rat)

71-36-3 butan-1-ol

Oral LD50 790 mg/kg (rat)
Dermal LD50 3,400 mg/kg (rabbit)
Inhalative LC50/4 h 8,000 mg/l (rat)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6,800 mg/kg (rat)
Dermal LD50 >3,400 mg/kg (rab)
Inhalative LC50/4 h >10.2 mg/l (rat)

78-92-2 butanol

Oral LD50 6,480 mg/kg (rat)

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)
Dermal LD50 2,000 mg/kg (rabbit)
Inhalative LC50/4 h 11 mg/l (ATE)

a mass reaction of ethyl benzene and xylene

Dermal LD50 1,100 mg/kg (ATE)
Inhalative LC50/4 h 11 mg/l (ATE)

(Contd. on page 9)
US

Trade name: SPRAY LENS CLEAR

(Contd. of page 8)

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral LD50 1,030 mg/kg (ATE)

- Primary irritant effect:
 - on the skin:
Causes skin irritation.
 - on the eye:
Causes serious eye damage.
- Sensitization:
May cause an allergic skin reaction.
- Additional toxicological information:

- Carcinogenic categories
- IARC (International Agency for Research on Cancer)

1330-20-7 xylene: 3

1330-20-7 xylene: 3

- NTP (National Toxicology Program)

None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- Specific target organ toxicity - single exposure
May cause respiratory irritation. May cause drowsiness or dizziness.
- Specific target organ toxicity - repeated exposure
May cause damage to organs through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.

* **12 Ecological information**

· **12.1 Toxicity**

· Aquatic toxicity: No further relevant information available.

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

· **12.5 Results of PBT and vPvB assessment**

· PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).

· vPvB: Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

* **13 Disposal considerations**

· **13.1 Waste treatment methods**

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)

Trade name: SPRAY LENS CLEAR

(Contd. of page 9)

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

14.1 UN-Number

· DOT, ADR, IMDG, IATA UN1950

14.2 UN proper shipping name

· DOT Aerosols, flammable
· ADR UN1950 AEROSOLS
· IMDG AEROSOLS
· IATA AEROSOLS, flammable

14.3 Transport hazard class(es)

· DOT



· Class 2.1 Gases
· Label 2.1
· ADR



· Class 2.5F Gases
· Label 2.1
· IMDG, IATA



· Class 2.1 Gases
· Label 2.1

14.4 Packing group

· DOT, ADR, IMDG, IATA Void

14.5 Environmental hazards:

· **14.6 Special precautions for user:** Warning: Gases

· Hazard identification number (Kemler code): -

· EMS Number: F-D,S-U

· Stowage Code SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre:
Category A. For AEROSOLS with a capacity above 1 litre:
Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre:

(Contd. on page 11)

Trade name: SPRAY LENS CLEAR

(Contd. of page 10)

Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

· ADR

· Excepted quantities (EQ)

Code: E0
Not permitted as Excepted Quantity

· IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ)

1L
Code: E0
Not permitted as Excepted Quantity

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

71-36-3 butan-1-ol

78-92-2 butanol

1330-20-7 xylene

1330-20-7 xylene

· TSCA (Toxic Substances Control Act):

115-10-6 dimethyl ether: ACTIVE

71-36-3 butan-1-ol: ACTIVE

64742-95-6 Solvent naphtha (petroleum), light arom.: ACTIVE

78-92-2 butanol: ACTIVE

1330-20-7 xylene: ACTIVE

104810-47-1 mix of: a-3-(3-(2H-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionyl-o-hydroxypoly(oxyethylene);a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-o-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene): ACTIVE

1761-71-3 4,4'-methylenebis(cyclohexylamine): ACTIVE

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine: ACTIVE

41556-26-7 bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate: ACTIVE

68937-54-2 Siloxanes and silicones, di-Me, 3-hydroxypropyl-Me, ethoxylated: ACTIVE

82919-37-7 methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate: ACTIVE

1330-20-7 xylene: ACTIVE

· Hazardous Air Pollutants

1330-20-7 xylene


1330-20-7 xylene

(Contd. on page 12)
US

Trade name: SPRAY LENS CLEAR

(Contd. of page 11)

- Proposition 65
- Chemicals known to cause cancer:
None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity for males:
None of the ingredients is listed.
- Chemicals known to cause developmental toxicity:
None of the ingredients is listed.
- Cancerogenity categories
- EPA (Environmental Protection Agency)
71-36-3 butan-1-ol: D
1330-20-7 xylene: I
1330-20-7 xylene: I
- TLV (Threshold Limit Value)
1330-20-7 xylene: A4
1330-20-7 xylene: A4
- NIOSH-Ca (National Institute for Occupational Safety and Health)
None of the ingredients is listed.
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labeled according to the CLP regulation.
- Hazard pictograms



- Signal word Danger
- Hazard-determining components of labeling:
butan-1-ol
Solvent naphtha (petroleum), light arom.
a mass reaction of ethyl benzene and xylene
3-aminomethyl-3,5,5-trimethylcyclohexylamine
4,4'-methylenebis(cyclohexylamine)
- Hazard statements
H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H302+H332 Harmful if swallowed or if inhaled.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
- Precautionary statements
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

(Contd. on page 13)
US

Trade name: SPRAY LENS CLEAR

(Contd. of page 12)

P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves / eye protection / face protection.
P301+P312	If swallowed: Call a poison center/doctor if you feel unwell.
P302+P352	If on skin: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P321	Specific treatment (see on this label).
P314	Get medical advice/attention if you feel unwell.
P330	Rinse mouth.
P362+P364	Take off contaminated clothing and wash it before reuse.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H226 Flammable liquid and vapor.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

· **Contact:**

H.B BODY S.A
Ms Olympia Stamkou
Ph: +30 2310 790 032
fax: +30 2310 790 033

· **Date of preparation / last revision 03/17/2023**

· * **Data compared to the previous version altered.**